



* WHERE CLADDING MANUFACTURER REQUIRES MORE THAN 100MM OF APRON UPSTAND UNDER CLADDING, CLADDING SUPPLIER TO SUPPLY AND INSTALL OVER FLASHING TO SUIT THEIR REQUIREMENTS.
FOR DETAILS REFER TO CLADDING MANUFACTURER.

Angle Bracket

150 Step Flashing

Gerard Roof Tile

Tile Batten 50x40mm

Rafter

Wall Cladding

Brick Tie

Wall Underlay / Building Wrap

Support nog

Minimum Upstand of Tile 40mm (minimum cover of over flashing 35mm)

Roofing Underlay (Carried up face of framing behind upstand flashing)

© 2020 Terms Of Use Disclaimer: This information is intended solely as a guide for the use of Gerard Roofs products. Before using you should ensure that the product is suitable for use in the specific application. Nothing in this information constitutes a statement of fitness for particular purpose and appropriate expert advice is to always be obtained. Gerard Roofs makes no warranty regarding the use of this information with non - Gerard Roofs products. This drawing is the property of Gerard Roofs. It cannot be copied in any form and must be returned to Gerard Roofs upon request. All Details are to be used for indicative purposes only. All dimenions in millimeters.



STANDARD GERARD ROOF TILES

WALL PARALLEL 150 STEP FLASHING DETAIL ON BATTENS

APPLICABLE TO THE FOLLOWING MODELS OF GERARD TILES:

CLASSIC	ROCKPORT
SHAKE	ALPINE
BOND	TUDOR
MILANO	ANTICA

Date:	July 2025	NZ: gerardroofs.co.nz
Version:	01	customerservice@gerardroofs.co.nz
Scale:	N.T.S.	AUS: gerardroofs.com.au
		info@gerardroofs.com.au
Code:	SFGAB_308C_TD_R01_02_2025	