

Wall Cladding

Building Wrap

Support nog

Minimum Upstand of Tile
40mm minimum cover of
over flashing 35mm

Roofing Underlay
(Carried up face of framing
behind upstand flashing)

* WHERE CLADDING MANUFACTURER REQUIRES MORE
THAN 100MM OF APRON UPSTAND UNDER CLADDING,
CLADDING SUPPLIER TO SUPPLY AND INSTALL OVER
FLASHING TO SUIT THEIR REQUIREMENTS.

FOR DETAILS REFER TO CLADDING MANUFACTURER.

104 Standard Side Wall Flashing

CF Shake

15mm min. thk
Structural Plywood

Rafter



CF SHAKE

TRANSVERSE SIDE WALL FLASHING DETAIL ON PLYWOOD

© 2020 Terms Of Use Disclaimer: This information is intended solely as a guide for the use of Gerard Roofs products. Before using you should ensure that the product is suitable for use in the specific application. Nothing in this information constitutes a statement of fitness for particular purpose and appropriate expert advice is to always be obtained. Gerard Roofs makes no warranty regarding the use of this information with non - Gerard Roofs products. This drawing is the property of Gerard Roofs. It cannot be copied in any form and must be returned to Gerard Roofs upon request. All Details are to be used for indicative purposes only. All dimensions in millimeters.

Date: June 2025

Version: 01

Scale: N.T.S.

Code:

NZ: [gerardroofs.co.nz](mailto:customerservice@gerardroofs.co.nz)
customerservice@gerardroofs.co.nz

AUS: [gerardroofs.com.au](mailto:info@gerardroofs.com.au)
info@gerardroofs.com.au

CFSKP_308C_TD_R01_09_2025